## **PFINDER 945 DRY POWDER DEVELOPER** FOR PENETRANT TESTING



## DESCRIPTION

PFINDER 945 is a dry powder developer for fluorescent penetrant testing. PFINDER 945 can be applied to the surface by dust storm cabinet, electrostatic equipment, etc.

Developer form a according DIN EN ISO 3452-1.

## APPLICATION

The capability of the penetrant system should be checked regularly by means of own reference pieces or e.g. reference test block 2 according EN ISO 3452-3.

Process description according DIN EN ISO 3452-1 see www.pfinder.com.



Version 7 | 14.02.2022 | Page 1/1



## YOUR GREEN NDT BENEFITS No hazard classification/labeling acc. to EC regulation Odourless

YOUR HANDLING + COST SAVING BENEFITS Excellent developing properties Easily removable with compressed air or water **APPROVALS & CONFORMITIES** 

The product conforms to these specifications / is suitable for the use according to:

EN ISO 3452-2 | VDA236-150 | ASTM E165 | ASME V Art.6 | ASTM E1417

PACKAGING	SHELF-LIFE & STORAGE
10-l-pail	5 years
These packages are on stock and instantly available. Other packages on demand.	Storage between + 5 °C and + 45 °C.

CHARACTERISTIC DATA	Specification	Unit	Value
Bulk density		kg/l	approx. 0,2